

KICKIT™

BILLET ALUMINUM KICKSTANDS

Thank you for your purchase! We are confident that you will be pleased with the quality of our product.

Instructions: 11-13 SXF250/350/450*12-13 SX125-300 (PMB-01-3006)

NOTE: We recommend using a thread-locking agent on all bolt threads.

- 1) You must modify the stock chain slider to accommodate the kickstand lower mounting spacer.
- 2) Remove the lower chain slider and bolt from the suspension linkage pivot.
- 3) Place the chain slider in a vise. Figure 1
- 4) Use a 1/2" drill bit in a drill press or a hand drill and enlarge the hole in the chain slider as shown in Figure 1, make sure your drill bit is parallel with the hole to ensure proper placement of the chain slider.
- 5) As you drill, the metal bushing will be pushed out the back side of the chain slider; this is normal and will aid you in enlarging the hole.
- 6) Insert the lower mounting spacer into the chain slider as shown in Figure 2.
- 7) Remove the lower sub-frame to main-frame bolt.
- 8) Install the kickstand onto the bike using the 8x30mm flat head bolt at the sub-frame to main-frame bolt location. Do not tighten yet.
- 9) Install the chain slider with the lower mounting adapter behind the lower kickstand mounting hole and insert the 8x80mm flat head bolt.
- 10) Periodically check all mounting bolts for tightness.

Maintenance:

Clean and lubricate the kickstand pivot area after each ride! We recommend using a heavy-duty chain lube, or WD-40. If necessary, you can remove the back cover plate for additional cleaning. Never remove the kickstand leg from the pivot pin! Do not use this kickstand as an aid when kick-starting your bike, it will cause premature damage.



Figure 1



Figure 2



PARTS LIST:

- 1-Kickstand
- 1-8x30 FH
- 1-8x80 FH
- 1-Adapter

Check out our Spark Arrestor Endcaps, Billet Cargo Racks, Shark Fins and other billet accessories at...

PROMOTO
BILLET.COM