



Thank you for your purchase, we are confident that you will be pleased with the quality of our product.

Kickstand Installation Instructions

2006-07 Yamaha YZ250/450F (4-strokes)

To install your new kickstand:

1. Remove the left foot peg and bracket using a Torx® size T-50 wrench or socket.
To ease bracket removal, use a heat gun to help loosen the factory installed thread-lock material.

NOTE: If you do not have the proper tools have your dealer install the kickstand.

2. Install the kickstand between the left foot peg bracket and the frame. Reinstall the foot peg bracket using the supplied longer bolts. We recommend using a removable thread-locking agent on the bolts.
3. Make sure that you tighten the foot peg bracket bolts to the correct torque as specified in your owner's manual.
4. Re-install the foot peg.
5. Periodically check the foot peg mounting bolts, and kickstand pivot bolt for tightness.

Maintenance: Clean and lubricate the kickstand pivot area after each ride. We recommend using a penetrating lube, such as WD-40. If necessary, you can remove the back cover plate for additional cleaning.

CAUTION: We do not recommend starting the bike with the kickstand down, as this may cause damage to the kickstand.

Manufactured and Distributed by:
Pro Moto Billet
11461 Lone Star Rd..
Nampa, ID 83651
208-466-4762

Check out our Spark Arrestor Endcaps, Billet Cargo Racks, Shark fins and other billet accessories at...

